

## IE-SW-ELB-08-8TX

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)



### Features of EcoLine Series B Switches

- Covers the most common port combinations with RJ45 and SFP ports for flexible usage
- Network availability is strongly increased thanks to Broadcast Storm Protection
- Support real time communication e.g. in PROFINET networks due to the "Quality of Service" functionality – "PROFINET Conformance Class A"
- Very small design for installation in places where space is critical
- A rotatable DIN-rail-clip allows use at locations offering very limited vertical space such as installation cabinets
- The AC voltage input enables use without a switching power supply to save cost in e.g. building automation
- Plastic-free, handling optimized packaging for fast processing and environmental friendliness

### General ordering data

|            |                                                                                          |
|------------|------------------------------------------------------------------------------------------|
| Version    | Network switch, unmanaged, Fast Ethernet, Number of ports: 8x RJ45, IP40, -10 °C...60 °C |
| Order No.  | <a href="#">2828550000</a>                                                               |
| Type       | IE-SW-ELB-08-8TX                                                                         |
| GTIN (EAN) | 4064675369875                                                                            |
| Qty.       | 1 Stück                                                                                  |

## IE-SW-ELB-08-8TX

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

www.weidmueller.com

## Technische Daten

### Dimensions and weights

|            |         |                 |            |
|------------|---------|-----------------|------------|
| Depth      | 64 mm   | Depth (inches)  | 2.52 inch  |
| Height     | 103 mm  | Height (inches) | 4.055 inch |
| Width      | 43.5 mm | Width (inches)  | 1.713 inch |
| Net weight | 195 g   |                 |            |

### Temperatures

|                     |                            |                       |                |
|---------------------|----------------------------|-----------------------|----------------|
| Storage temperature | -40 °C...85 °C             | Operating temperature | -10 °C...60 °C |
| Humidity            | 5 to 95 % (non-condensing) |                       |                |

### EMC conformity and approvals

|                 |                                                                                                                                                                                                                                                                                                  |           |                                                            |
|-----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|------------------------------------------------------------|
| EMC standards   | EN 55032, EN 55024, CISPR 32, FCC Part 15 Subpart B Class A, IEC 61000-4-2 ESD: Contact: 4 kV; Air: 8 kV, IEC 61000-4-3 RS: 80 MHz bis 1 Ghz: 3 V/m, IEC 61000-4-4 EFT: Power: 0.5 kV; Signal: 0.5 kV, IEC 61000-4-5 Surge: Power: 0.5 kV; Signal: 1 kV, IEC 61000-4-6 CS: 3 Vrms, IEC 61000-4-8 | Free fall |                                                            |
| Safety standard | UL 61010-1, UL 61010-2-201                                                                                                                                                                                                                                                                       | Shock     | According to IEC 60068-2-31<br>according to IEC 60068-2-27 |
| Vibration       | according to IEC 60068-2-6                                                                                                                                                                                                                                                                       |           |                                                            |

### Environmental conditions

|                             |                            |                 |  |
|-----------------------------|----------------------------|-----------------|--|
| Humidity                    | 5 to 95 % (non-condensing) |                 |  |
| Operating altitude          | Altitude, max.             | 2,000 m         |  |
|                             | Note                       | in acc. with UL |  |
| Operating temperature, max. | 60 °C                      |                 |  |
| Operating temperature, min. | -10 °C                     |                 |  |
| Storage temperature, max.   | 85 °C                      |                 |  |
| Storage temperature, min.   | -40 °C                     |                 |  |

### Guarantee

|               |         |
|---------------|---------|
| Time interval | 5 years |
|---------------|---------|

### Interfaces

|                     |                                                                                                          |               |                                                                               |
|---------------------|----------------------------------------------------------------------------------------------------------|---------------|-------------------------------------------------------------------------------|
| Function DIP switch | 1x for enabling QoS (according to IEEE 802.1p), 1x for enabling/disabling the broadcast storm protection | LED indicator | Power LED: PWR, Port LED: LNK/ACT, 10/100M (RJ45 port)                        |
| Number of ports     | 8x RJ45                                                                                                  | RJ45 ports    | 10/100BaseT(X), auto negotiation, Full-/half-duplex mode, Auto MDI/MDI-X port |

## IE-SW-ELB-08-8TX

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technische Daten

## MTBF

|      |                              |                  |
|------|------------------------------|------------------|
| MTBF | According to Standard        | Telcordia SR-332 |
|      | Operating time (hours), min. | 463,836 h        |

## Management features

|                        |                                                     |                             |                                                |
|------------------------|-----------------------------------------------------|-----------------------------|------------------------------------------------|
| Network traffic filter | Quality of Service (QoS),<br>Class of Service (CoS) | Industrial protocol support | PROFINET device acc. to<br>conformance class A |
|------------------------|-----------------------------------------------------|-----------------------------|------------------------------------------------|

## Power supply

|                             |                                        |        |
|-----------------------------|----------------------------------------|--------|
| Connection type             | 1 removable 2-pin terminal block       |        |
| Current consumption         | Voltage                                | 24 V   |
|                             | Current                                | 0.13 A |
| Overload current protection | Yes                                    |        |
| Reverse polarity protection | Yes                                    |        |
| Voltage supply              | 12/24/48 V DC, 24 V AC, 1 single input |        |
| Voltage supply range        | Voltage type                           | DC     |
|                             | Voltage, min.                          | 9.6 V  |
|                             | Voltage, max.                          | 60 V   |
|                             | Voltage type                           | AC     |
|                             | Voltage, min.                          | 18 V   |
|                             | Voltage, max.                          | 36 V   |

## Switch characteristics

|                     |            |                 |     |
|---------------------|------------|-----------------|-----|
| Bandwidth backplane | 1.6 Gbit/s | MAC table size  | 1 K |
| Packet buffer size  | 448 Kbit   | Priority queues | 2   |

## Technical data

|                       |               |                   |           |
|-----------------------|---------------|-------------------|-----------|
| Housing main material | Metal         | Protection degree | IP40      |
| Speed                 | Fast Ethernet | Switch            | unmanaged |
| Type of mounting      | DIN rail      |                   |           |

## Technology

|                |                                                                                                                                                                    |              |                          |
|----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|--------------------------|
| Data switching | Store and Forward                                                                                                                                                  | Flow control | IEEE 802.3x flow control |
| Standard       | IEEE 802.3 for 10BASE-T,<br>IEEE 802.3u for 100BASE-<br>TX, IEEE 802.3x for flow<br>control, IEEE 802.1p for<br>Class of Service / Quality<br>of Service (CoS/QoS) |              |                          |

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000734    | ETIM 7.0    | EC000734    |
| ETIM 8.0    | EC000734    | ETIM 9.0    | EC000734    |
| ETIM 10.0   | EC000734    | ECLASS 9.0  | 19-17-01-06 |
| ECLASS 9.1  | 19-17-01-06 | ECLASS 10.0 | 19-17-04-02 |
| ECLASS 11.0 | 19-17-04-02 | ECLASS 12.0 | 19-17-04-02 |
| ECLASS 13.0 | 19-17-04-02 | ECLASS 14.0 | 19-17-04-02 |
| ECLASS 15.0 | 19-17-04-02 |             |             |

## IE-SW-ELB-08-8TX

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technische Daten

## Environmental Product Compliance

|                                      |                                      |
|--------------------------------------|--------------------------------------|
| RoHS Compliance Status               | Compliant with exemption             |
| RoHS Exemption (if applicable/known) | 6c, 7a, 7cl                          |
| REACH SVHC                           | Lead 7439-92-1                       |
| SCIP                                 | 95f06c58-199a-4ab7-817c-c2503ba62133 |

## Approvals

Approvals



|                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|-----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Approvals MAMID | <a href="https://mdcop.weidmueller.com/mediadelivery/rendition/900_319222/-T1z1mm-S800/">https://mdcop.weidmueller.com/mediadelivery/rendition/900_319222/-T1z1mm-S800/</a> <a href="https://mdcop.weidmueller.com/mediadelivery/rendition/900_319228/-T1z1mm-S800/">https://mdcop.weidmueller.com/mediadelivery/rendition/900_319228/-T1z1mm-S800/</a> <a href="https://mdcop.weidmueller.com/mediadelivery/rendition/900_319245/-T1z1mm-S800/">https://mdcop.weidmueller.com/mediadelivery/rendition/900_319245/-T1z1mm-S800/</a> <a href="https://mdcop.weidmueller.com/mediadelivery/rendition/900_319260/-T1z1mm-S800/">https://mdcop.weidmueller.com/mediadelivery/rendition/900_319260/-T1z1mm-S800/</a> |
|-----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

|                         |            |
|-------------------------|------------|
| ROHS                    | Conform    |
| UL File Number Search   | UL Website |
| Certificate no. (cULus) | E141197    |

## Downloads

|                                             |                                                                                                                                                                                 |
|---------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Approval/Certificate/Document of Conformity | <a href="#">KC certificate</a><br><a href="#">EU Declaration of Conformity</a><br><a href="#">UK Declaration of Conformity</a><br><a href="#">RCM Declaration of Conformity</a> |
| Engineering Data                            | <a href="#">CAD data – STEP</a>                                                                                                                                                 |
| User Documentation                          | <a href="#">Hardware Installation Guide</a><br><a href="#">Application notes – Industrial Product Security Guideline</a>                                                        |
| Catalogues                                  | <a href="#">Catalogues in PDF-format</a>                                                                                                                                        |

**IE-SW-ELB-08-8TX****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Accessories****Mounting kit for 19" rack assembly**

- For assembling DIN rail-based devices on 19" racks

**General ordering data**

|            |                            |                           |
|------------|----------------------------|---------------------------|
| Type       | RM-KIT                     | Version                   |
| Order No.  | <a href="#">1241440000</a> | Kit for 19"-rack mounting |
| GTIN (EAN) | 4050118029154              |                           |
| Qty.       | 1 Stück                    |                           |